

BID ON 2020/2021 TRUCK EQUIPMENT & PLOW:

The City reserves the right to accept or reject any and all bids

DUMP BODY

- | Y | N | |
|--------------------------|--------------------------|---|
| <input type="checkbox"/> | <input type="checkbox"/> | 1. Unibody design, no cross members |
| <input type="checkbox"/> | <input type="checkbox"/> | 2. 11 ft. box w/84 in. inside width |
| <input type="checkbox"/> | <input type="checkbox"/> | 3. 30 in. sides w/38 in. tailgate (minimum) |
| <input type="checkbox"/> | <input type="checkbox"/> | 4. 10 gauge 201 stainless steel sides, ends, cab shield, side braces, front and rear post (minimum) |
| <input type="checkbox"/> | <input type="checkbox"/> | 5. 7 gauge stainless steel tailgate and braces |
| <input type="checkbox"/> | <input type="checkbox"/> | 6. One piece 3/16 AR400 180,000 psi floor (minimum) |
| <input type="checkbox"/> | <input type="checkbox"/> | 7. Side sheets formed to floor, not a weld in radius |
| <input type="checkbox"/> | <input type="checkbox"/> | 8. Fully boxed and welded top rails |
| <input type="checkbox"/> | <input type="checkbox"/> | 9. Rub rails sloped |
| <input type="checkbox"/> | <input type="checkbox"/> | 10. Two in. board pockets |
| <input type="checkbox"/> | <input type="checkbox"/> | 11. Two 8 in. steel I-beam long sills (minimum) - no splices |
| <input type="checkbox"/> | <input type="checkbox"/> | 12. Air trip tailgate |
| <input type="checkbox"/> | <input type="checkbox"/> | 13. Stainless steel steps on left side |
| <input type="checkbox"/> | <input type="checkbox"/> | 14. Oval stop turn, tail holes in rear post (LED) |
| <input type="checkbox"/> | <input type="checkbox"/> | 15. Oval LED strobe light holes in rear post |
| <input type="checkbox"/> | <input type="checkbox"/> | 16. One stainless steel shovel holder |
| <input type="checkbox"/> | <input type="checkbox"/> | 17. Underside of body to be under-coated |
| <input type="checkbox"/> | <input type="checkbox"/> | 18. Greasable box and tailgate pins |
| <input type="checkbox"/> | <input type="checkbox"/> | 19. All electrical connections in heat shrink tubing |
| <input type="checkbox"/> | <input type="checkbox"/> | 20. Four mud flaps for rear tires |
| <input type="checkbox"/> | <input type="checkbox"/> | 21. Mounted and fully operational |

UNDERBODY HOIST

- | Y | N | |
|--------------------------|--------------------------|----------------------------|
| <input type="checkbox"/> | <input type="checkbox"/> | 1. Telescopic hoist |
| <input type="checkbox"/> | <input type="checkbox"/> | 2. Seventeen ton (minimum) |
| <input type="checkbox"/> | <input type="checkbox"/> | 3. Greasable pivot points |
| <input type="checkbox"/> | <input type="checkbox"/> | 4. Body props |

HYDRAULIC SYSTEM

- | Y | N | |
|--------------------------|--------------------------|---|
| <input type="checkbox"/> | <input type="checkbox"/> | 1. Front mount, crank shaft driven 6.0 cubic inch load sense pump w/shutoff valve |
| <input type="checkbox"/> | <input type="checkbox"/> | 2. Valve body to run hoist, plow-up, plow reverse, auger, spinner |
| <input type="checkbox"/> | <input type="checkbox"/> | 3. Cable system controls |
| <input type="checkbox"/> | <input type="checkbox"/> | 4. Single lever for plow-up and plow reverse |
| <input type="checkbox"/> | <input type="checkbox"/> | 5. Cushion valve for plow |
| <input type="checkbox"/> | <input type="checkbox"/> | 6. Force America 5100EX electric/hydraulic spreader controls |
| <input type="checkbox"/> | <input type="checkbox"/> | 7. Valve body located on side of truck frame in stainless steel enclosure |
| <input type="checkbox"/> | <input type="checkbox"/> | 8. Twenty gallon minimum stainless steel Hyd. Tank w/filter and sight gauge |
| <input type="checkbox"/> | <input type="checkbox"/> | 9. Shut-off valve at tank |
| <input type="checkbox"/> | <input type="checkbox"/> | 10. Mounted and fully operational |

(continued on next page)

STAINLESS STEEL TAILGATE SPREADER

- | Y | N | |
|--------------------------|--------------------------|---|
| <input type="checkbox"/> | <input type="checkbox"/> | 1. Six inch auger |
| <input type="checkbox"/> | <input type="checkbox"/> | 2. Seven gauge construction |
| <input type="checkbox"/> | <input type="checkbox"/> | 3. Tailgate spill shields on inside of tailgate |
| <input type="checkbox"/> | <input type="checkbox"/> | 4. Low speed, high torque drive motor |
| <input type="checkbox"/> | <input type="checkbox"/> | 5. 18 inch self-leveling poly spinner |
| <input type="checkbox"/> | <input type="checkbox"/> | 6. Quick attach and detach |
| <input type="checkbox"/> | <input type="checkbox"/> | 7. Quick couplers |
| <input type="checkbox"/> | <input type="checkbox"/> | 8. Mounted and fully operational |

LIGHTS

- | Y | N | |
|--------------------------|--------------------------|--|
| <input type="checkbox"/> | <input type="checkbox"/> | 1. Plow lights w/turn signals, mounted on stainless steel brackets |
| <input type="checkbox"/> | <input type="checkbox"/> | 2. Two LED strobe mounted on cab guard |
| <input type="checkbox"/> | <input type="checkbox"/> | 3. Two rear box post-mounted LED strobes |
| <input type="checkbox"/> | <input type="checkbox"/> | 4. One sander light (All lights must be installed to factory installed switches) |

REQUIRED

- | Y | N | |
|--------------------------|--------------------------|--|
| <input type="checkbox"/> | <input type="checkbox"/> | 1. Heavy-duty steel plate and pestle hitch on rear of truck w/safety chain holders |
| <input type="checkbox"/> | <input type="checkbox"/> | 2. Automatic ice chains |
| <input type="checkbox"/> | <input type="checkbox"/> | 3. No more than 90 days to complete after delivery of cab and chassis |
-

PLOW

- | Y | N | |
|--------------------------|--------------------------|--|
| <input type="checkbox"/> | <input type="checkbox"/> | 1. Eleven foot length |
| <input type="checkbox"/> | <input type="checkbox"/> | 2. 43 inch minimum height |
| <input type="checkbox"/> | <input type="checkbox"/> | 3. 10 gauge steel moldboard (minimum) |
| <input type="checkbox"/> | <input type="checkbox"/> | 4. Heavy duty push frame |
| <input type="checkbox"/> | <input type="checkbox"/> | 5. Minimum of 6 hinge points |
| <input type="checkbox"/> | <input type="checkbox"/> | 6. Four adjustable trip springs on moldboard, plus cutting edge trip |
| <input type="checkbox"/> | <input type="checkbox"/> | 7. Ten fully welded ribs |
| <input type="checkbox"/> | <input type="checkbox"/> | 8. Two heavy duty reversing cylinders |
| <input type="checkbox"/> | <input type="checkbox"/> | 9. 3/4 x 8 standard AA SHO punch cutting edge |
| <input type="checkbox"/> | <input type="checkbox"/> | 10. Wrap-around curb guards |
| <input type="checkbox"/> | <input type="checkbox"/> | 11. Pin and loop style hitch |
| <input type="checkbox"/> | <input type="checkbox"/> | 12. Level lift design |
| <input type="checkbox"/> | <input type="checkbox"/> | 13. Single or double acting cylinder w/float |
| <input type="checkbox"/> | <input type="checkbox"/> | 14. Plow end markers |
| <input type="checkbox"/> | <input type="checkbox"/> | 15. Twelve inch rubber snow flap |
| <input type="checkbox"/> | <input type="checkbox"/> | 16. Adjustable parking stand |
| <input type="checkbox"/> | <input type="checkbox"/> | 17. Quick couplers |
| <input type="checkbox"/> | <input type="checkbox"/> | 18. Painted black |
| <input type="checkbox"/> | <input type="checkbox"/> | 19. Mounted and fully operational |